



WEVER & DUCRÉ  
LIGHTING

# PIRRO SURFACE 4.0

151451B3

Project \_\_\_\_\_

Type \_\_\_\_\_

Notes \_\_\_\_\_

Quantity \_\_\_\_\_

Date \_\_\_\_\_

## GENERAL

Ceiling \_\_\_\_\_

Surface \_\_\_\_\_

Jet Black \_\_\_\_\_

IP20 \_\_\_\_\_

Interior \_\_\_\_\_

1520 lm \_\_\_\_\_

9005<sup>a</sup> \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

3-step binning \_\_\_\_\_

## PHYSICAL

Length 182 mm \_\_\_\_\_

Width 50 mm \_\_\_\_\_

Height 80 mm \_\_\_\_\_

0.48 kg \_\_\_\_\_

## ELECTRICAL

incl. PS | phase-cut dim \_\_\_\_\_



220 - 240 V \_\_\_\_\_

Total connected power 18 W \_\_\_\_\_

PC1 \_\_\_\_\_

Safety distance 0.3 m \_\_\_\_\_

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.





**WEVER & DUCRÉ**  
LIGHTING

# PIRRO

## SURFACE 4.0

151451B3

### Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.92	0.88	0.83	0.79	0.76
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

### OPTICAL

#### Honeycomb

TYPE	COLOUR	(MM)	ORDERCODE
CENO   PIRRO   BLIEK PETIT	Pure White	29	9 0 0 5 1 1 3 0
CENO   PIRRO   BLIEK PETIT	Signal Black	29	9 0 0 5 1 1 3 1

