



WEVER & DUCRÉ
LIGHTING

DEEP ADJUST 1.0 PAR16

112320B0

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Recessed

Jet Black

IP20

Interior

320 lm

9005^a

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

OPTICAL

Wide Flood

Beam angle 48°

PHYSICAL

Diameter 94 mm

Height 102 mm

0.21 kg

Standard Springs

Tilt min 35°

Tilt max 35°

Rotation 355°

ELECTRICAL

100 - 240 V

Total connected power 8.6 W

PC2

Safety distance 0.3 m

CUTOUT



Diameter 86-89 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 23 mm

Recessed depth 105 mm

^a RAL Palette colors may deviate slightly due to production conditions.



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

DEEP ADJUST 1.0 PAR16

112320B0

CONE DIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	451	0.89
2	113	1.78
3	50	2.67
4	28	3.56
5	18	4.45

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 3
3000K GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 5
2700K GU10	Signal White	ø50-58	9 0 1 2 2 8 W 2
2700K GU10	Signal White	ø50-58	9 0 1 2 2 8 W 3
3000K GU10	Signal White	ø50-58	9 0 1 2 2 8 W 4

PAR16 LED Lamp | Ambient

TYPE	Ø · H (MM)	ORDERCODE
1800-2850K GU10	ø50-58	9 0 1 2 2 9 S 9

MOUNTING

Spring clip

TYPE	COLOUR	(MM)	ORDERCODE
MR16 LED PAR16 max. 12W		59	7 3 2 4 0 2 0 3
MR16 LED PAR16 max. 12W	Pure White		7 3 2 4 0 6 5 1
MR16 LED PAR16 max. 12W	Signal Black		7 3 2 4 0 6 5 2
MR16 LED PAR16 max. 12W	Gold		7 3 2 4 0 9 4 0
MR16 LED PAR16 max. 12W	Grey		7 3 2 4 0 9 4 1
MR16 LED PAR16 max. 12W	Copper		7 3 2 4 0 9 4 2