



WEVER & DUCRÉ
LIGHTING

PIRRO SURFACE 4.1

151461B3

Project _____

Type _____

Notes _____

Quantity _____

Date _____

GENERAL

Ceiling _____

Surface _____

Jet Black _____

IP20 _____

Interior _____

1520 lm _____

9005^a _____

LED

2700 K _____

3-step binning _____

PHYSICAL

Length 94 mm _____

Width 94 mm _____

Height 80 mm _____

0.5 kg _____

ELECTRICAL

incl. PS | phase-cut dim _____


220 - 240 V _____

Total connected power 18 W _____

PC1 _____

Safety distance 0.3 m _____

^a RAL Palette colors may deviate slightly due to production conditions.





WEVER & DUCRÉ
LIGHTING

PIRRO SURFACE 4.1

151461B3

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.92	0.88	0.83	0.79	0.76
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL

Honeycomb

TYPE	COLOUR	(MM)	ORDERCODE
CENO PIRRO BLIEK PETIT	Pure White	29	9 0 0 5 1 1 3 0
CENO PIRRO BLIEK PETIT	Signal Black	29	9 0 0 5 1 1 3 1

