



WEVER & DUCRÉ
LIGHTING

PIRRO SURFACE 2.0

151251E3

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Surface

Signal White + Jet Black

IP20

Interior

760 lm

LED

2700 K

3-step binning

PHYSICAL

Length 94 mm

Width 50 mm

Height 80 mm

0.3 kg

ELECTRICAL



incl. PS | phase-cut dim

220 - 240 V

Total connected power 9 W

PC1

Safety distance 0.3 m





WEVER & DUCRÉ
LIGHTING

PIRRO SURFACE 2.0

151251E3

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.92	0.88	0.83	0.79	0.76
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL

Honeycomb

TYPE	COLOUR	(MM)	ORDERCODE
CENO PIRRO BLIEK PETIT	Pure White	29	9 0 0 5 1 1 3 0
CENO PIRRO BLIEK PETIT	Signal Black	29	9 0 0 5 1 1 3 1

