



WEVER & DUCRÉ  
LIGHTING

# STIPO 2.0

737267Y4

Project

Type

Notes

Quantity

Date

## GENERAL

Floor

Surface

Grey Brown

IP65

Exterior

505 lm

RAL 8019<sup>a</sup>

## LED

3000 K

CRI 80

L70 / 50000 h

3-step binning

## OPTICAL

Beam angle 39°

## PHYSICAL

Diameter 52 mm

Height 120 mm

0.49 kg

Tilt min 135°

Tilt max 135°

## ELECTRICAL

220 - 240 V

Total connected power 7.3 W


PC2

Safety distance 0.3 m


<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.



IP65 □ ↻ ↺ ↻ ↻ 0,3 m



## LIGHT DISTRIBUTION



[737267Y4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.  
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ  
LIGHTING

# STIPO 2.0

737267Y4

## CONE DIAGRAM

39°

h (m)	E0° (lx)	ø (m)
1	1070	0.71
2	267	1.43
3	119	2.14
4	66	2.86
5	42	3.57

## GROUND SPIKE

### Ground Spike

TYPE	Ø · H (MM)	ORDERCODE
STAKE 1.0   STIPO	ø122 · 357	9 0 0 1 3 1 0 6