



Lap



Milan



Lap 80 C.



Ø 800 | H. 330 mm
 3 x E27 Standard bulb
 Retrofit LED Code 2298 12 W
 1100 (x3) lumen | 2.700 K
 Dimmable
 Class I: Basic insulation

Finishes

6719 ● Ribbon shade in raw
 3719 colour

Lap 80 S.



Ø 800 x 330 | H. 1400 mm
 3 x E27 Standard bulb
 Retrofit LED Code 2298 12 W
 1100 (x3) lumen | 2.700 K
 Dimmable
 Class I: Basic insulation

Finishes

6719 ● Ribbon shade in raw
 3719 colour
 2719

DOWNLOADS

Catalogue

[Lap](#)

3D Files

[6719 + 3719](#)
[6719 + 3719 + 2719](#)

3D Max Files

[6719 + 3719](#)
[6719 + 3719 + 2719](#)

Assembly instructions

[6719 + 3719](#)
[6719 + 3719 + 2719](#)

Photometric curve

[6719 + 3719](#)
[6719 + 3719 + 2719](#)

Economic efficiency index

[6719 + 3719](#)
[6719 + 3719 + 2719](#)

An warm play of contrasting light

Lap 80 C.

Translucent decorative lampshade by means of a handcrafted cinning system, in a raw color finish. Central lampshade in 35 cm diameter acid-satin opal triplex blown glass. Base and rear-base in machined steel. Matt white lacquered finish (RAL 9016). Fixing of the decorative screen using a magnet system.

Lap 80 S.

Translucent decorative lampshade by means of a handcrafted cinning system, in a raw color finish. Central lampshade in 35 cm diameter acid-satin opal triplex blown glass. Base where shades are affixed in machined steel. Matt white lacquered finish (RAL 9016). Mechanized steel ceiling mounting base. Matte black lacquer finish (RAL 9005). Fixing of the decorative screen using a magnet system. Steel cables that help regulate the desired height in the pendant thanks to the system enabled in the ceiling base.