



Amid



Milan



Amid 78 F.



610 x 303 mm | H. 780 mm
 1 x E27 Standard bulb
 Retrofit LED Code 2298 12 W
 1100 (x1) lumens | 2.700 K
 Dimmable
 Class I: Basic insulation
 Protection degree against
 dust and water: IP55

Finishes

6717 ● Matt black lacquering
 (RAL 9005)

Amid 106 F.



802 x 368 mm | H. 1.060 mm
 1 x E27 Standard bulb
 Retrofit LED Code 2298 12 W
 1100 (x1) lumens | 2.700 K
 Dimmable
 Class I: Basic insulation
 Protection degree against
 dust and water: IP55

Finishes

6718 ● Matt black lacquering
 (RAL 9005)

DOWNLOADS

Catalogue

[Amid](#)

3D Files

[6717](#)

[6718](#)

3D Max Files

[6717](#)

[6718](#)

Assembly instructions

[6717 / 6718](#)

Photometric curve

[6717](#)

[6718](#)

Economic efficiency index

[6717](#)

[6718](#)

Creating atmosphere
 with light

Translucent decorative lampshade by means of a handcrafted cinning system, in polyscreen anti-UVA resistant to outdoor conditions. Central lampshade in 25 cm diameter acid-satin opal triplex blown glass. Base for glass diffuser screen support in machined

steel. Matte white lacquer finish (RAL9016) with zinc plating treatment for protection in outdoor conditions. Screen fixing arms in matt black lacquer (RAL 9005) with cataphoresis treatment for protection in outdoor conditions. Electrical cord length: 3 meters.