

Product Code 00-6670-05-05 Installation Instructions 3D File Photometry Revit (BIM)



Alive Single

Francesc Vilaró

Pendant Alive Single LED 8.5 LED warm-white 2700K ON-OFF Black 492lm

Technical features

Luminaire total power: 8.5W

Real lumens: 492 Real Im/W: 58

Correlated Colour Temperature (CCT): LED warm-white 2700K

Structure material: Aluminium, Steel

Structure finish: Black

Diffuser material: Methacrylate

Diffuser finish: Tinted

Voltage / frequency: 100-277V/50-60Hz

Dimming protocol: ON-OFF

Power Factor: 0.90

THD%: 20

Useful life: 50,000h L80B20

Warranty: 5 años












Luminotechnic features

CRI: 80

MacAdam steps: 2

Photobiological risk: RG1

Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	6.9W	LED warm- white 2700K






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 00-6670-05-05

Installation Instructions 3D File Photometry Revit (BIM)



Alive Single

Francesc Vilaró

Pendant Alive Single LED 8.5 LED warm-white 2700K ON-OFF Black 492lm

Logistics



Net weight (kg): 0.62 Packaged weight (kg): 1.1

Packaging: 135mm x 135mm x 505mm

Light application



Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.